

Data Sheet

Fujitsu Server PRIMERGY TX140 S2 Mono-Socket Intel® Xeon® processor server

Datasheet for Red Hat certification

Expandable all-round server for SMEs

FUJITSU Server PRIMERGY systems provide the most powerful and flexible data center solutions for companies of all sizes, across all industries and for any type of workload. This includes expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as density-optimized scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, and provide more agility in daily operations in order to turn IT faster into a business advantage.

Perfect for small and medium businesses as well as branch offices, FUJITSU Server PRIMERGY TX tower systems are robust and cost-efficient servers by providing rock solid reliability. Additionally they are characterized by simple IT operations, low power consumption and quiet operation so that they can be handled by non-technically trained staff and can be used in standard office environments. By the way: Almost all PRIMERGY TX servers can be rack-mounted to offer best flexibility.

PRIMERGY TX140 S2

The PRIMERGY TX140 S2 is the ideal robust and cost-efficient server for small and medium-sized businesses (SMB) or branch offices. It offers best Intel® Xeon® E3 performance and solid expandability thanks to hot-plug storage drives. The optionally redundant power supply and a choice of different RAID controllers ensure high availability and peace of mind. Thanks to its compact housing and extremely low operating noise the server is ideally suited for showrooms or offices, for example under the desk. The

optional support of legacy PCI adapter cards makes the PRIMERGY TX140 S2 optimally suited for special solutions, such as telephone or security systems. Furthermore, the comprehensive Fujitsu ServerView® Suite provides support for administrators during server installation, deployment and administration. The PRIMERGY TX140 S2: an excellent long-term investment.



Features & Benefits

Main Features	Benefits
Cost-effective performance and availability <ul style="list-style-type: none">■ Latest Intel® Xeon® E3 v3 series technology■ Optionally redundant power supply unit	<ul style="list-style-type: none">■ Increased performance of up to 15 % compared to the previous generation■ Optimized for classic server tasks like business applications, file, print or databases■ Redundant power supply units for peace of mind
Optimized for SMEs <ul style="list-style-type: none">■ Low noise emissions through optimized air flow and Fujitsu's Cool-Safe™ technology■ New compact 4 U chassis■ Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control	<ul style="list-style-type: none">■ Silent operation for use in offices or showrooms■ So small and silent that it might even be placed under desks■ The comprehensive tools of the Fujitsu ServerView Suite eases the administrator's life
Lifecycle investment protection <ul style="list-style-type: none">■ Solid scalability of up to 4 DIMMs with 32 GB memory, up to 8 storage drives and 4 PCI slots■ Optional support for legacy PCI cards■ Optional tower to rack conversion kit and extensive connectivity options	<ul style="list-style-type: none">■ Meet today's demand and be prepared for future requirements■ Support for special solutions like telephone or security systems■ The TX140 S2 grows as your company grows, making it an excellent long-term investment

Technical details

PRIMERGY TX140 S2

Base unit	PRIMERGY TX140 S2 LFF	PRIMERGY TX140 S2 SFF	PRIMERGY TX140 S2 LFF	PRIMERGY TX140 S2 SFF
Housing types	Tower	Tower	Tower	Tower
Storage drive architecture	3.5-inch	2.5-inch	3.5-inch	2.5-inch
Power supply	Standard	Standard	Hot-plug	Hot-plug

Mainboard

Mainboard type	D3239
Chipset	Intel® C224
Processor quantity and type	1 x Intel® Xeon® processor E3-1200v3 product family

Processor

Processor	Intel® Xeon® processor E3-1220v3 (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 80 W)
Processor	Intel® Xeon® processor E3-1230v3 (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 80 W)
Processor	Intel® Xeon® processor E3-1240v3 (4C/8T, 3.40 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 80 W)
Processor	Intel® Xeon® processor E3-1265Lv3 (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 45 W)
Processor	Intel® Xeon® processor E3-1270v3 (4C/8T, 3.50 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 80 W)
Processor	Intel® Xeon® processor E3-1280v3 (4C/8T, 3.60 GHz, TLC: 8 MB, Turbo: Yes, 1,600 MHz, 82 W)

Memory slots	4
Memory slot type	DIMM (DDR3) UDIMM
Memory capacity (min. - max.)	4 GB - 32 GB
Memory protection	ECC

Memory options	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank 8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank
----------------	--

Memory modules notes	1333MHz or 1600 MHz memory modules
----------------------	------------------------------------

Interfaces

USB 2.0 ports	6 (4x external rear, 2x internal for UFM or backup device, no USB wakeup supported)
USB 3.0 ports	4 (2x external rear, 2x external front)
Graphics (15-pin)	1 analog graphics interface derived from iRMC (up to 1600x1200 or 1920x1080 at 16bpp)
Serial connection	1 x serial RS-232-C, usable for iRMC or system or shared
LAN / Ethernet	2 x1 Gb/s Ethernet; RJ45
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port

Onboard or integrated Controller

RAID controller	Optionally integrated RAID 0/1 or RAID 5/6 controller for SAS base units (occupies one PCIe slot). additional RAID controller options are described under Components RAID controller
SATA Controller	Intel® C224, 2 ports used for accessible drives 4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux;
LAN Controller	Intel® i217 + Intel® i210 onboard, 2 x 10/100/1000 Mbit/s Ethernet, Intel® i217LM: 2xTX/2xRX, iSCSI remote boot support, APM wake up. Intel® i210, 4xTX/4xRX, iSCSI and PXE 2.0-remote Boot via LAN, WoL. Service LAN: Realtek RTL8211E
Remote Management Controller	Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller) IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / 1.2 (option)

Slots

PCI-Express 3.0 x8	1 x (up to 240 mm length)
PCI-Express 2.0 x1 (mech. x4)	1 x (up to 167 mm length)
PCI-Express 2.0 x4 (mech. x8)	1 x (up to 167 mm length)
PCI-Express 2.0 x8	1 x (up to 240 mm length)
Slot Notes	In SAS configuration 1x PCI-Express occupied by modular RAID controller. In configurations with Intel® Core™ i3 or Intel® Pentium® processors slots are operated with PCI-Express 2.0.

Drive bays

Storage drive bays	3.5-inch or 2.5-inch hot-plug SAS/SATA
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	all possible options described in relevant system configurator

Drive bays (Base unit specific)

Storage drive bays	Max. 4x 3.5-inch	Max. 8x 2.5-inch
Accessible drive bays	3 x 5.25/1.6-inch for 1 x backup drive + 1 x ODD	3 x 5.25/1.6-inch for 1 x backup drive + 1 x ODD

General system information

Number of fans	1
Fan configuration	1 standard fan
Fan notes	non redundant / non hot-plug

Operating panel

Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (orange / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow) CSS (yellow)

BIOS

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager Remote PXE boot support Remote iSCSI boot support
---------------	---

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Server® 2012 Foundation
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows Server® 2008 R2 Foundation
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
Red Hat® Enterprise Linux 6	
Red Hat® Enterprise Linux 5	
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	ServerView Suite - Deploy
	SV Installation Manager
	SV Scripting Toolkit
	ServerView Suite - Control
	Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart)
	Agents and CIM Providers
	System Monitor
	RAID Manager
	Capacity Management
	Power Management
Option	Storage Support
	ServerView Suite - Maintain
	Remote Management (iRMC)
	Update Management (BIOS, Firmware, Windows Drives and SV Agents)
	Performance Measurement
	Asset Management
	Online Diagnostics
	ServerView Suite - Integrate
	Integration packs e.g. for Microsoft System Center, VMware vCenter, Nagios, HP SIM and others
	Deployment Solutions and others
ServerView Suite - Maintain	
iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media	
ServerView Suite - Integrate	
Integration pack for Fujitsu ManageNow® solution	

Dimensions / Weight

Floor-stand (W x D x H)	177 x 560 x 455 mm
Rack (W x D x H)	483 x 495 x 175 mm
Dimension notes	Floorstand Width 306 mm with tilt protection; depth measured excludes handles on redundant PSU. Rack depth excludes handles of redundant PSU and rack front.
Mounting Depth Rack	543 mm
Height Unit Rack	4 U
Weight	Rack: 12.5kg - 20kg; Tower: 15kg - 23 kg
Weight notes	Actual weight may vary depending on configuration

Dimensions / Weight

Rack integration kit	Rack integration kit can be ordered as option
----------------------	---

Environmental

Operating ambient temperature	10 - 35 °C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 - Guideline for Data Center (installation specification)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Sound pressure (LpAm)	SATA: 25 dB(A) idle mode/ 25 dB(A) operation mode; SAS: 31 dB(A) idle mode/ 34 dB(A) operation mode
Sound power (LWAd; 1B = 10dB)	SATA: 4.2 B idle mode/ 4.2 B operation mode ; SAS: 4.8 B idle mode/ 5.2 B operation mode
Noise notes	Noise emissions and operation modes depend on system configuration.

Electrical values

Power supply configuration	1x standard, 1x hot-plug or 2x redundant hot-plug
Max. output of single power supply	450 W
Standard power supply output	300 W (90% efficiency)
Hot-plug power supply output	450 W (94% efficiency)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	6 A / 3 A (100 V / 240 V)
Active power (min. configuration)	23 W
Active power (max. configuration)	203 W
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/
Apparent power (max. configuration)	247 VA
Heat emission	730.8 kJ/h (692.7 BTU/h)
Power Supply Notes	The active power and apparent power values may change according to configuration.

Compliance

Germany	GS
Europe	CE Class A *
USA/Canada	CSA us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI
Russia	GOST-R
South Korea	KC
China	CCC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance notes	* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

Compliance

Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Germany	GS
Europe	CE Class A *

Compliance	
USA/Canada	CSA us ULc/us FCC Class A
Japan	VCCI
Russia	GOST-R
South Korea	KC
China	CCC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Compliance notes	* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Storage drives	
SSD SATA, 6 Gb/s, 400 GB, MLC, hot-plug, 2.5-inch, enterprise	
SSD SATA, 6 Gb/s, 200 GB, MLC, hot-plug, 2.5-inch, enterprise	
SSD SATA, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise	
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 3.5-inch, economic	
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical	
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, hot-plug, 3.5-inch, economic	
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical	
HDD SATA, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical	
HDD SAS, 6 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise	
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise	
HDD SAS, 6 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise	
HDD SAS, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical	
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise	
HDD SAS, 6 Gb/s, 450 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise	
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise	
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise	
HDD SAS, 6 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise	
HDD SAS, 6 Gb/s, 146 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise	
HDD SAS, 6 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SAS, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SAS, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical	
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical	
Backup Drives	
LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s	
LTO5HH Ultrium, 1,500 GB, 140 MB/s, half height, SAS 6Gb/s	
LTO6HH Ultrium, 2,500 GB, 160 MB/s, half height, SAS 6Gb/s	
RDX Drive, 320 GB, 500 GB, 1 TB, 25 MB/s, half height, USB 3.0	

Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM ; 8x DVD; 24x CD), slimline, SATA I DVD-ROM, (16xDVD; 48xCD), half height, SATA I DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
SCSI / SAS Controller	SAS Ctrl. 6 Gbit/s 8 ports int. PCIe 2.0 x8
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU for selected systems (based on LSI SAS2108) RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116C), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208) RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), 8 ports int. RAID level: 0, 1, 10, No BBU support
Communication, Network	Ethernet Ctrl. 1 x 1 Gbit/s PCIe 1.1 x1 (Intel®) Ethernet Ctrl. 1 x 1 Gbit/s PCIe x4 (Intel®) Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.0 x8 (Fujitsu) Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.1 x8 (Intel®) Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 (Fujitsu) Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 (Fujitsu)
Warranty	
Standard Warranty	1 year
Service level	Onsite Service
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM
Maintenance and Support Services - the perfect extension	
Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX140 S2, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX140 S2, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2014-05-21 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions